

CBPL Serisi ŞOK Evaporatörleri

Model	Yüzey m ²	Uygun Fan Tipi		SC 5 (-40 Evap./-34 Oda)	(-45C Evap./-40 Oda)
		Ad.	Çap. Ø	(kW)	(kW)
CBPL 63.1.11	65,5	1x1	630	10,8	8,1
CBPL 63.1.21	80,6	2x1	630	15,6	11,5
CBPL 63.2.21	107	2x1	630	18,4	13,6
CBPL 63.3.21	131	2x1	630	20,5	15,2
CBPL 63.1.31	120	3x1	630	21	17,4
CBPL 63.2.31	159	3x1	630	28,5	21,2
CBPL 63.3.31	200	3x1	630	32,5	24,6



Model	Ölçüler						ISITICI watt				
							BATARYA		TAVA		Fan
	L	H1	H2	A	B	C	Asıl	Yedek	Asıl	Yedek	
CBPL 63.1.11	1.500	1.030	1.220	540	600	795	3x2150	2x2150	2x2150	1x2150	1x300
CBPL 63.1.21	2.300	1.030	1.220	540	600	795	6x2150	4x2150	5x2150	2x2150	2x300
CBPL 63.2.21	2.300	1.030	1.220	540	600	795	8x2150	6x2150	5x2150	2x2150	2x300
CBPL 63.3.21	2.770	1.030	1.220	540	600	795	10x2150	5x2150	5x2150	2x2150	2x300
CBPL 63.1.31	3.430	1.030	1.220	600	705	705	10x3150	5x3150	6x3150	2x3150	3x300
CBPL 63.2.31	3.430	1.030	1.220	540	675	705	12x3150	6x3150	6x3150	2x3150	3x300
CBPL 63.3.31	3.430	1.030	1.220	600	660	855	14x3150	7x3150	6x3150	2x3150	3x300

